

Printing date 08.07.2015 Version number 2 Revision: 08.07.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Antifreeze GW-12 (-40°C)

· Article number: 39140

 $\cdot$  1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Antifreeze

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

SWD Lubricants GmbH & Co.KG

Am Schlütershof 26 D-47059 Duisburg

Tel: 0049 (0)203 31919-0 Fax: 0049 (0)203 31919-99 E-mail:info@swd-gmbh.de

· Further information obtainable from:

Department product safety sdb@swd-gmbh.de

· 1.4 Emergency telephone number:

Informationszentrale gegen Vergiftungen Uni - Klinikum Bonn; Notfall - Nr.: +49 228 19 240

# SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

*Repr.* 2 H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Acute Tox. 4 H302 Harmful if swallowed.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS07 GHS08

- · Signal word Warning
- · Hazard-determining components of labelling: ethanediol
- · Hazard statements

H302 Harmful if swallowed.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

(Contd. on page 2)



Printing date 08.07.2015 Version number 2 Revision: 08.07.2015

Trade name: Antifreeze GW-12 (-40°C)

(Contd. of page 1)

P103 Read label before use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P281 Use personal protective equipment as required.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- $\cdot$  **PBT:** Not applicable.
- · vPvB: Not applicable.

# SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous compone	nts:	
		50-100%
EINECS: 203-473-3	🔷 STOT RE 2, H373; 🕠 Acute Tox. 4, H302	
	Sodium 2-ethylhexanoate	< 2.5%
EINECS: 243-283-8	🚸 Repr. 2, H361d	

- · SVHC None
- · Additional information: For the wording of the listed risk phrases refer to section 16.

## **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray.

*Use fire extinguishing methods suitable to surrounding conditions.* 

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbonmonoxide and Carbondioxide

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

(Contd. on page 3)



Printing date 08.07.2015 Version number 2 Revision: 08.07.2015

Trade name: Antifreeze GW-12 (-40°C)

(Contd. of page 2)

· Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

## SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep people at a distance and stay on the windward side.

· 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Storage in a collecting room is required.
- $\cdot$  7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

### 107-21-1 ethanediol

WEL Short-term value: 104\*\* mg/m³, 40\*\* ppm

Long-term value: 10\* 52\*\* mg/m<sup>3</sup>, 20\*\* ppm

Sk \*particulate \*\*vapour

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 4)



Printing date 08.07.2015 Version number 2 Revision: 08.07.2015

Trade name: Antifreeze GW-12 (-40°C)

(Contd. of page 3)

## · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

## · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

## · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Not suitable are gloves made of the following materials: Leather gloves
- · Eye protection: Goggles recommended during refilling

9.1 Information on basic physical a	and chemical properties
General Information Appearance:	clear
Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value at 20 °C:	8.6
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (DIN 51751)
Pour point	Not applicable
Flash point:	> 100 °C (DIN ISO 2592)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	410 °C (DIN 14522)
Decomposition temperature:	Not determined.
Self-igniting:	Not determined.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vape mixtures are possible.
Explosion limits:	
Lower:	3.2 Vol % (DIN EN 1839)
Upper:	53.0 Vol % (DIN EN 1839)
Vapour pressure at 20 °C:	23 hPa
Density at 20 °C:	1.0616 g/cm³ (DIN 51757)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Fully miscible.



Printing date 08.07.2015 Version number 2 Revision: 08.07.2015

Trade name: Antifreeze GW-12 (-40°C)

(Contd. of page 4)

· Viscosity:

Dynamic: Not determined. Kinematic: Not determined.

· Solvent content:

0.0 % Organic solvents: 42.0 % Water:

No further relevant information available. · 9.2 Other information

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions

Reacts with strong acids and oxidising agents.

Reacts with strong oxidising agents.

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

# SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

٠.	<i>LD/LC50</i>	values	rei	levant j	for	classification	:
----	----------------	--------	-----	----------	-----	----------------	---

## 107-21-1 ethanediol

LD50 5840 mg/kg (rat) Dermal LD50 9530 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion/irritation No irritant effect.
- · Serious eve damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us. Harmful

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

CMR effects (carcenogenic, mutagenic and toxicity for reproduction) are not known for these products.

Repr. 2

# SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

## 107-21-1 ethanediol

EC50 6500 mg/kg (Alg)

13000 mg/kg (SwF)

9300 mg/kg (daphnia)

(Contd. on page 6)



Printing date 08.07.2015 Version number 2 Revision: 08.07.2015

Trade name: Antifreeze GW-12 (-40°C)

(Contd. of page 5)

- · 12.2 Persistence and degradability Easily biodegradable
- · 12.3 Bioaccumulative potential

Due to the distribution coefficient n-octanol/water an accumulation in organisms is not expected.

- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

# SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Delivery of waste oil to offically authorised collectors only.

- · Uncleaned packaging:
- · Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

· Recommended cleansing agents: Water, if necessary together with cleansing agents.

14.1 UN-Number ADR, ADN, IMDG, IATA	Void	
	voiu	
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDĞ, İATA	Void	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Anne	ex II of	
MARPOL73/78 and the IBC Code	Not applicable.	

# SECTION 15: Regulatory information

- $\cdot$  15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 7)

(Contd. of page 6)



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.07.2015 Version number 2 Revision: 08.07.2015

Trade name: Antifreeze GW-12 (-40°C)

· Hazard pictograms



GHS0/ GHS08

- · Signal word Warning
- · Hazard-determining components of labelling:

Contains: ethane-1,2diol

ethanediol

### · Hazard statements

H302 Harmful if swallowed.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P281 Use personal protective equipment as required.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

H302 Harmful if swallowed.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

- · Department issuing MSDS: Product safety
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Acute Tox. 4: Acute toxicity, Hazard Category 4

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

- · Sources Concawe Product Dossier No.97/108. Concawe Product Dossier Nn. 01/54.
- \* Data compared to the previous version altered.